G5 T8 LED Tube

Ballast & AC Compatible | 2-ft & 4-ft

Features

- Safest LED T8 on the market
- Double-end wired with safety switches
- Ballast compatible
- AC Line Voltage friendly
- Patented safety design for anti-shock protection
- Patented replaceable driver to extend LED tube life to 10 years
- Available in 4-ft and 2-ft, all colors
- Universal driver (110V-277V)
- The SureFit tube comes with a field replaceable driver
- Works with shunted and non-shunted sockets

Product Compliance & Certifications:

- UL and cUL Type A/Type B listed (OOLV/OOLV7.E479597)
- UL and cUL classified (IFAR/IFAR7.E325073)
- DLC 4.2 qualified

Specifications

Size	2-ft, 4-ft
Lens Type	Clear, Diffused
Driver Style	Field-replaceable internal driver
Ballast	Instant Start
Efficacy	Clear lens ≥ 140 lm/w Diffused Lens ≥ 120 lm/w
Color	2700K, 3000K, 3500K 4000K, 5000K, 6000K
CRI	> 80
Input Voltage	110V-277V (50-60Hz)
Operating Temp.	-20ºF to 122ºF
Power Consumption	w/o ballast 2-ft@10W, 4-ft@15W w ballast 2-ft@12W, 4-ft@17.5W
Light Output	Clear @ 2100lm Diffused @ 1800lm
Beam Angle	180º
Warranty	5-year warranty/50,000 hours

Description

Maintenance personnel can now easily insert a G5 SureFit tube in a fixture just like they would do for an ordinary T8 fluorescent. When the ballast fails, electricians may bypass the ballast for further energy savings. When wired double ended on line voltage, patented saftey switches on both ends make the G5 tube the safest LED T8 on the market.

DOUBLE-END WIRED W/ SAFETY SWITCHES
Patented safety switches protect an installer from electric shock hazard, unlike some products on the market, the G5 works with existing T8/T12 sockets, shunted or non-shunted. Furthermore, adds an additional fail safe in case of accidental future fluorescent reinsertion by custodial staff.

AC-LINE VOLTAGE FRIENDLY
It works with direct input voltage from 110V to 277V

THE SUREFIT TUBE
It has a field replaceable driver. You may opt to purchase the field replaceable driver at time of product purchase, effectively extending the product's warranty from 5 years to 10 years. Standard warranty is 5 years/50,000 hours

DARE-YOU-TO-TOUCH-IT TEST
If the other manufacturer inserts one end of their tube into a live fixture and will not touch the pins of the exposed end, then it is not a safe product.

aleddra

425.430.4555 | info@aleddra.com | sales@aleddra.com | www.aleddra.com

2-ft Ordering Information

Model #	Size	Lens	Wattage	Lumen	Color
LLT-2-T8-10W-DBA-D-27K	2-ft	Diffused	10W	1100lm	2700K
LLT-2-T8-10W-DBA-D-30K	2-ft	Diffused	10W	1100lm	3000K
LLT-2-T8-10W-DBA-D-35K	2-ft	Diffused	10W	1100lm	3500K
LLT-2-T8-10W-DBA-D-40K	2-ft	Diffused	10W	1200lm	4000K
LLT-2-T8-10W-DBA-D-50K	2-ft	Diffused	10W	1200lm	5000K
LLT-2-T8-10W-DBA-D-60K	2-ft	Diffused	10W	1200lm	6000K
LLT-2-T8-10W-DBA-C-27K	2-ft	Clear	10W	1300lm	2700K
LLT-2-T8-10W-DBA-C-30K	2-ft	Clear	10W	1300lm	3000K
LLT-2-T8-10W-DBA-C-35K	2-ft	Clear	10W	1300lm	3500K
LLT-2-T8-10W-DBA-C-40K	2-ft	Clear	10W	1400lm	4000K
LLT-2-T8-10W-DBA-C-50K	2-ft	Clear	10W	1400lm	5000K
LLT-2-T8-10W-DBA-C-60K	2-ft	Clear	10W	1400lm	6000K

4-ft Ordering Information

Model #	Size	Lens	Wattage	Lumen	Color
LLT-4-T8-15W-DBA-D-27K	4-ft	Diffused	15W	1650lm	2700K
LLT-4-T8-15W-DBA-D-30K	4-ft	Diffused	15W	1650lm	3000K
LLT-4-T8-15W-DBA-D-35K	4-ft	Diffused	15W	1650lm	3500K
LLT-4-T8-15W-DBA-D-40K	4-ft	Diffused	15W	1800lm	4000K
LLT-4-T8-15W-DBA-D-50K	4-ft	Diffused	15W	1800lm	5000K
LLT-4-T8-15W-DBA-D-60K	4-ft	Diffused	15W	1800lm	6000K
LLT-4-T8-15W-DBA-C-27K	4-ft	Clear	15W	1950lm	2700K
LLT-4-T8-15W-DBA-C-30K	4-ft	Clear	15W	1950lm	3000K
LLT-4-T8-15W-DBA-C-35K	4-ft	Clear	15W	1950lm	3500K
LLT-4-T8-15W-DBA-C-40K	4-ft	Clear	15W	2100lm	4000K
LLT-4-T8-15W-DBA-C-50K	4-ft	Clear	15W	2100lm	5000K
LLT-4-T8-15W-DBA-C-60K	4-ft	Clear	15W	2100lm	6000K