

PRODUCT DESCRIPTION

Designed with architecturally minded approach. While minimal in profile, the Flood 1 series stands out wherever it's installed. Be it illuminating a flag, accenting a wall, or providing security, it's a perfect combination of form and function.

FEATURES

- Slim design
- Aluminum construction
- IP65 Rated

PERFORMANCE RATINGS AND CERTIFICATIONS

ETL, cETL, RoHS Compliant

PERFORMANCE SUMMARY

Lumens: 3,630 (30W)

Lumens per Watt: 120

CRI-Minimum: >70

Operating Environment: -40 _ to 40 _

IP Rating: IP65

PRODUCT IMAGE(S)



KIT INFORMATION

Finish: Aluminum, bronze finish

Mounting: Knuckle (standard), Handle
Yoke, Pipe Adapter

Dimensions: 8.11" x 2.93" x 5.56"

ELECTRICAL SYSTEM CHARACTERIZATIONS

Voltage: 120 - 277VAC to 480VAC

Dimming: 0-10V (Optional)

Power Factor: >0.9

THD: <20%

WARRANTY

5 Year Standard Warranty Limited

ORDERING MATRIX

Example: ST-SL-L-600W-30-15D-MT-SGR1

Family	Product	Watts	Color Temp	Beam Angle	Voltage	Options
ST	ST-FL-1S					

ST	ST-FL-1S	20W 30W	30 = 3000K 40 = 4000K 50 = 5000K		MT = 120-277V HV = 480V	BPC = Button Photocell 010V = 0-10V Dimming TV = Top Visor BV = Bottom Visor WG = Wire Guard
----	----------	------------	--	--	----------------------------	--

PHOTOMETRICS

DIMENSIONS

(inch/mm)

