

## PRODUCT DESCRIPTION

Traditional wall mounted luminaires providing efficient LED lighting for commercial and industrial applications. Fixtures are constructed with a corrosion resistant diecast aluminum housing and powder coat paint finish. Available in full cut off and half cut off light distribution as well as 4000K and 5000K color temperatures.



## FEATURES

- ETL
- IP65 Rated
- Stainless Steel Screws
- 5 Year Warranty

## PERFORMANCE RATINGS AND CERTIFICATIONS

ETL

## PERFORMANCE SUMMARY

**Lumens:** 13,614

**Lumens per Watt:** 114

**CRI-Minimum:** >70

**Operating Environment:** -40°C to 40°C

**IP Rating:** IP65

## KIT INFORMATION

**Finish:** Corrosion resistant, rugged die-cast aluminum housing with powder coat paint finish

**Mounting:** Wall mount

**Dimensions:** 18.4" x 9.1" x 9.4"

## ELECTRICAL SYSTEM CHARACTERIZATIONS

**Voltage:** 120VAC-277VAC

**Dimming:** 0-10V (Optional)

**Power Factor:**

**THD:**

## WARRANTY

5 Year Standard Warranty Limited






## ORDERING MATRIX

Example: ST-SL-L-600W-30-15D-MT-SGR1

Family	Product	Watts	Color Temp	Beam Angle	Voltage	Options
ST	ST-WP-02A					

ST	ST-WP-02A	120W	40 = 4000K 50 = 5000K		MT = 120-277V	PC1 = Photo Cell 120VAC PC2 = Photo Cell 277VAC SRG1 = 100-277VAC Surge Protection 010V = 0-10V Dimming
----	-----------	------	--------------------------	--	---------------	--

## PHOTOMETRICS



Isofootcandle plots = ALL Models in 5000K CCT  
@ 10' (3.048 m) mounting height.  
Distances are in units of mounting height.