

PRODUCT DESCRIPTION

Traditional wall mounted luminaires providing efficient LED lighting for commercial and industrial applications. Fixtures are constructed with a corrosion resistant diecast aluminum housing and powder coat paint finish. Available in full cut off and half cut off light distribution as well as 4000K and 5000K color temperatures.

FEATURES

- ETL, IP65 Rated
- Stainless Steel Screws
- 5 Year Warranty

PERFORMANCE RATINGS AND CERTIFICATIONS

ETL

PERFORMANCE SUMMARY

Lumens: 4,909 (40W), 6,904 (60W), 8,637 (80W)

Lumens per Watt: 110

CRI-Minimum: >70

Operating Environment: -40°C to 40°C

IP Rating: IP65



KIT INFORMATION

Finish: Corrosion resistant, rugged die-cast aluminum housing with powder coat paint finish.

Mounting: Wall mount

Dimensions: 14.21" x 9.13" x 11.41"

ELECTRICAL SYSTEM CHARACTERIZATIONS

Voltage: 120VAC-277VAC

Dimming: 0-10V (Optional)

Power Factor:

THD:

WARRANTY

5 Year Standard Warranty Limited

ORDERING MATRIX


Example: ST-SL-L-600W-30-15D-MT-SGR1

Family	Product	Watts	Color Temp	Beam Angle	Voltage	Options
ST	ST-WP-04A					


ST	ST-WP-04A	40W 60W 80W	40 = 4000K 50 = 5000K		MT = 120-277V	PC1 = Photo Cell 120VAC PC2 = Photo Cell 277VAC SRG1 = 100-277VAC Surge Protection 010V = 0-10V Dimming
----	-----------	-------------------	--------------------------	--	---------------	------------------------------------------------------------------------------------------------------------------

PHOTOMETRICS


- LEGEND
- 0.1 fc
 - 0.5 fc
 - 1.0 fc
 - 5.0 fc



40W (Type 5)



60W (Type 5)



80W (Type 5)

Isofootcandle plots = ALL Models in 5000K CCT @ 10' (3.048 m) mounting height. Distances are in units of mounting height.